


# MATERIAL SAFETY DATA SHEET

Issue Date: 1/05

Supersedes: 5/04



## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTITY: **SEALOFLEX CT PINK™**  
 PRODUCT USE: **Flexible Waterproofing System**  
 MANUFACTURED BY: **Sealoflex® Dichtungssysteme GmbH**  
**Headoffice:** Bei der Kirche 2  
 25474 Ellerbek  
 Tel. 04101-38 30 73  
 Fax 04101-38 30 74  
**Production:** Leipziger Str. 106-112  
 04439 Engelsdorf  
 Tel. 0341-252 3895  
 Fax 0341-252 3895  
 e-mail: sealoflex@t-online.de

## 2. COMPOSITION & INFORMATION ON INGREDIENTS

| Component                          | % weight    | CAS #       | SARA Title III<br>Section 313 | RCRA | CARCINOGENICITY<br>(As per 29CFR 1910.1200) | State Right-To-Know |     |    |
|------------------------------------|-------------|-------------|-------------------------------|------|---|---------------------|-----|----|
|                                    |             |             |                               |      |   | PA                  | NJ  | MA |
| Styrene Copolymer                  | 14.0 – 22.0 | Proprietary | Not Listed                    | No   | No  | No                  | No  | No |
| Aliphatic Petroleum<br>Distillates | 40.0 – 45.0 | 64742-89-8  | Not Listed                    | No   | No  | Yes                 | Yes |    |
| Benzene                            | <3ppm       | 71-43-2     |                               | D018 | Yes   | Yes                 | Yes |    |
| Pigments, Fillers &<br>Extenders   | 38.0 – 40.0 | N.A.        | Not Listed                    | No   | No  | No                  | No  |    |
| Additives                          | <0.5        | N.A.        | Not Listed                    | No   | No  | No                  | No  |    |

All components are listed in the TSCA inventory.

## 3. PHYSICAL AND CHEMICAL PROPERTIES

|                   |                            |                                      |                             |
|-------------------|----------------------------|--------------------------------------|-----------------------------|
| Physical State    | <b>Pink Viscous Liquid</b> | Bulk Density                         | <b>No Data</b>              |
| Odor              | <b>Aliphatic</b>           | Vapor Pressure                       | <b>&gt;10 mm/Hg @ 68 °F</b> |
| Odor Threshold    | <b>Not Applicable</b>      | Vapor Density                        | <b>Heavier than Air</b>     |
| Molecular Formula | <b>No Data</b>             | Evaporation Rate (n-Butyl Acetate=1) | <b>&gt;1</b>                |
| Molecular Weight  | <b>No Data</b>             | VOC content                          | <b>40 - 45%</b>             |
| Boiling Point     | <b>&gt;250 °F</b>          | % Volatiles                          | <b>40 - 45%</b>             |
| Freezing Point    | <b>Not Applicable</b>      | Solubility in Water                  | <b>Not Soluble</b>          |
| Specific Gravity  | <b>1.07</b>                | Viscosity (cps)                      | <b>3000 - 5000</b>          |
| Density (lbs/gal) | <b>8.9</b>                 | pH                                   | <b>Not Applicable</b>       |

## 4. STABILITY & REACTIVITY

GENERAL: **This product is stable under normal conditions.**

CONDITIONS TO AVOID: **Sources of ignition and heat.**

INCOMPATIBLE MATERIAL: **Avoid strong oxidizing agents.**

HAZARDOUS POLYMERIZATION: **Will not occur.**

HAZARDOUS DECOMPOSITION PRODUCTS: **May form oxides of carbon, various hydrocarbons.**

**5. HAZARD IDENTIFICATION**

POTENTIAL HEALTH EFFECTS: **THIS IS A FLAMMABLE PRODUCT**  
 SARA 311/312 Hazard Class: Acute, Fire

EYE CONTACT: Risk of serious damage to eyes. May cause permanent damage if eye is not immediately irrigated. Symptoms include stinging, tearing, and redness.

SKIN CONTACT: Repeated or prolonged exposure may induce skin irritation. Symptoms may include redness, burning, drying and cracking of skin, and chemical burns.

INGESTION: Ingestion will cause moderate to severe irritation or chemical burns to the gastrointestinal tract. Injury may be severe and cause death. Acute oral toxicity is LD<sub>50</sub> 3038 mg/Kg.

INHALATION: Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may cause chemical pneumonia. Symptoms usually occur at air concentrations higher than the recommended exposure limits.

**6. FIRST AID MEASURES**

EYE CONTACT: If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

SKIN CONTACT: Immediately flush skin with plenty of clean running water while removing contaminated clothing. Continue for at least 15 minutes. If symptoms persist, seek medical attention. Launder clothing before reuse.

INHALATION: If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet and seek medical attention.

INGESTION: **DO NOT** induce vomiting. Seek immediate medical attention. Place individual on the left side with the head down. Refer to medical personnel or take direction from a physician or poison control center. Never give anything by mouth to an unconscious person.

**7. FIRE FIGHTING MEASURES**

GENERAL: This is a flammable product. Increased temperature may increase pressure in closed containers resulting in rupture, spreading fire and increasing risk of injury.

|                                |  |             |
|--------------------------------|--|-------------|
| FLASHPOINT AND METHOD:         | 50 °F (TCC)  |             |
| FLAMMABLE LIMITS (NAPHTHA)     | Lower: 0.9%  | Upper: 7.0% |
| AUTOIGNITION TEMPERATURE:      | 450 °F (232 °C)  |             |
| HAZARDOUS COMBUSTION PRODUCTS: | Oxides of carbon and nitrogen, various hydrocarbons.                                 |             |
| EXTINGUISHING MEDIA:           | Foam, CO <sub>2</sub> , dry chemical   |             |
| FIRE FIGHTING INSTRUCTIONS:    | Wear self-contained breathing apparatus with full facepiece and protective clothing. |             |

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

|                      |                         |  |
|----------------------|-------------------------|--|
| EXPOSURE GUIDELINES: | ACGIH                   | OSHA                                     |
| <b>NAPHTHA:</b>      | 300ppm TWA              | 300ppm TWA, 400ppm STEL                  |
| <b>BENZENE:</b>      | 0.5ppm TWA, 2.5ppm STEL | 1 ppm TWA, 5ppm STEL, Action Level .5ppm |

RECOMMENDED PERSONAL PROTECTIVE EQUIPMENT:

RESPIRATORY: **If the workplace exposure limit(s) is exceeded, a NIOSH/MSHA approved respirator is advised in the absence of adequate environmental control.**

EYES: **Chemical splash goggles.**

SKIN: **Wear resistant gloves, impervious clothing and boots.**

OTHER: **Provide sufficient mechanical ventilation (general and/or local) to maintain exposure below exposure guidelines.**

**9. HANDLING AND STORAGE**

STORAGE TEMPERATURE: **40 - 90°F (4 - 32°C)**

STORAGE: **Keep container tightly closed. Store in a cool well ventilated area away from heat, sources of ignition and strong oxidizing agents.**

HANDLING: **Open in a well ventilated area. Avoid breathing vapors. Prevent skin and eye contact. Empty containers should be disposed of according to local regulations.**

**10. ACCIDENTAL RELEASE MEASURES**

SMALL SPILL: **Eliminate all ignition sources (flares, flames, pilot lights, electrical sparks). Wearing recommended protective clothing, dike spill using soil, sand or compatible commercial absorbent. Pick up bulk of product using pumps or vacuum truck or absorb product in sand or commercial absorbent. Place in chemical waste containers for recovery or disposal.**

LARGE SPILL: **Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from the spill area until clean up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If run-off occurs, notify authorities as required. Pump or vacuum-transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent soil and other material to containers for disposal. Ensure that all local, State and Federal regulations are complied with for release reporting, recovery and disposal of material and containers.**

**11. DISPOSAL CONSIDERATIONS**

RCRA 40 CFR 261 CLASSIFICATION: Exhibits the characteristic of ignitability, toxicity for benzene.

U.S. EPA WASTE NUMBER/DESCRIPTION: D001, D018

DISPOSAL METHOD: Incinerate in an approved facility. Do not incinerate closed containers. Dilute with clean, low viscosity fuel. Untreated material should not be released to the environment.

CONTAINER DISPOSAL: Empty container retains potentially hazardous residue. Observe all hazard precautions. Remove all product residue from container and puncture or otherwise destroy empty container before disposal.

**12. TRANSPORTATION INFORMATION**

DOT INFORMATION – 49 CFR 172.101

DESCRIPTION: Flammable Liquid, N.O.S., 3, UN1993, II

CONTAINER MODE: One and five-gallon metal pails

NOS COMPONENT: Petroleum Distillates

*This Material Safety Data Sheet is provided as an information resource only. It should not be taken as a warranty or representation for which Sealoflex® Inc. assumes legal responsibility. While Sealoflex® Inc. believes the information contained herein is accurate and compiled from sources believed to be reliable, it is the responsibility of the user to investigate and verify its validity. The buyer assumes all responsibility of using and handling the product in accordance with applicable federal, state and local regulations.*