

Sealobond Primer WB

Penetrating Primer

Description

Sealobond Primer WB is a deep penetrating low viscosity clear primer intended for chalky surfaces or where surface adhesion presents difficulties.

Uses

Sealobond Primer WB is designed to penetrate and wet out chalky or oxidized surfaces introducing a tough acrylic resin into the substrate to bind the surface to form a sound substrate to accept top coats of various types thus providing improved adhesion to the substrate. Typical applications are:

- Priming older existing paint surfaces which have a chalky surface
- Priming concrete or masonry surfaces
- Gypsum
- Galvanised metal

Advantages

Sealoflex Primer WB displays the following characteristics:

- Penetrates readily into the substrate
- Easy to apply
- Forms a sound substrate suitable for coating
- Dries quickly
- Alkali resistant

Coverage

Sealobond Primer:

ca. 6m² / 1 litre

Instructions for Use

Surface Preparation

- All surfaces must be clean, dry and free from oil, grease or loosely adhering particles.
- On concrete surfaces apply Sealobond Primer WB to prime surface for overcoating.
- Apply by brush, roller or airless spray equipment.
- Allow to dry 24 hours.

Cleaning

Wash tools and equipment immediately after use with water.

Technical Data

Colour:	Milky White Dries clear
Storage:	5°C to 55°C
Shelf Life:	12 months if unopened and stored between 5°C to 32°C
Density:	200 gms / litre
Packaging	5 Ltr, 10 Ltr, & 20 Ltr Buckets